

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously presented) A sterile air trolley comprising a mobile casing having at least one air inlet in its lower region and a plurality of air outlets in its upper region, and enclosing an impeller operative to move air in through the at least one inlet, through a filter and out of the casing by way of the outlets, the upper region of the casing providing a substantially horizontal work surface, the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall being hollow and extending fully around the perimeter of the work surface whereby the filtered air is directed into the boundary wall and is emitted through air outlets in the boundary wall consisting essentially of air outlets facing inwardly of the boundary wall over the work surface from opposing sides, forming a continuously replenished rising layer of filtered air over the work surface.
2. (Currently amended) A sterile air trolley as claimed in claim 1, wherein the sterile/filtered air is directed across the work surface from all directions inwardly of the boundary wall and forms a the continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall.
3. (Cancelled)
4. (Previously presented) A sterile air trolley as claimed in claim 1, wherein the shape of the tray is rectangular, with the boundary wall defining the four sides of the rectangle and wherein the filtered air is emitted inwardly over the work surface from all four sides.
5. (Previously presented) A sterile air trolley as claimed in claim 4, wherein the trolley casing is in a modular form having a base unit housing the impeller and an upper

unit comprising the tray-shaped work surface and boundary wall, the upper unit being readily demountable from and re-mountable to the base unit.

6. (Currently amended) A sterile air trolley as claimed in claim 5, ~~wherein~~ further comprising sterilized surgical instruments ~~are~~ set out on the work surface of the upper unit and sealed in by a film, foil or lid of barrier material that is mounted above the work surface.

7. (Previously presented) A sterile air trolley as claimed in claim 6, wherein the height of the boundary wall is slightly greater than the height of the any of the instruments or other items placed flat on the work surface of the tray in order to fully enshroud the same.

8. (Previously presented) A sterile air trolley as claimed in claim 6, wherein the height of the boundary wall is on the order of 200 to 300mm while maintaining the blanket of sterile air.

9. (Previously presented) A sterile air trolley as claimed in claim 1, wherein the rate of flow of air from the outlets is of the order of 0.4 to 0.5 meters per second, and no less than approximately 0.35 meters per second.

10. (Original) A sterile air trolley as claimed in claim 9, wherein that part of the boundary wall comprising the air outlets is in the form of a mesh or is densely perforated with many substantially uniformly distributed apertures to provide a substantially uniform flow of air through the boundary wall.

11. (Previously presented) A sterile air trolley as claimed in claim 10, wherein the construction of the part of the boundary wall comprising the outlets is such as to provide a pressure drop of the order of at least 10 pascals.

12. (Previously presented) A sterile air trolley having a sterile air cabinet comprising a casing having at least one air inlet in its lower region and a plurality of air outlets in its upper region, and enclosing an impeller operative to move air in through the at least one inlet, through filter means and out of the casing by way of the outlets, the upper region of the casing providing a substantially horizontal work surface, the work surface having an upstanding boundary wall extending fully around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall being hollow whereby the filtered air is directed into the boundary wall and is emitted through air outlets in the boundary wall consisting essentially of air outlets facing inwardly of the boundary wall over the work surface from opposing sides, forming a continuously replenished rising layer of filtered air over the work surface.

13. (Cancelled)

14. (Previously presented) A sterile air trolley comprising a mobile casing having at least one air inlet in its lower region and a plurality of air outlets in its upper region, and enclosing an impeller operative to move air in through the at least one inlet, through a filter and out of the casing by way of the outlets, the upper region of the casing providing a substantially horizontal work surface, the work surface having an upstanding boundary wall extending around its perimeter whereby the work surface and boundary wall form a tray, the boundary wall being hollow and extending fully around the perimeter of the work surface whereby the filtered air is directed into the boundary wall and is emitted through air outlets in the boundary wall over the work surface from opposing sides forming a continuously replenished rising layer of filtered air over the work surface, the air outlets facing only substantially inwardly towards the work surface from the boundary wall.

15. (Currently amended) A sterile air trolley as claimed in claim 14, wherein the sterile/filtered air is directed across the work surface from all directions inwardly of the

boundary wall and forms ~~a~~the continuously replenished rising layer of filtered air over the work surface within the sterile zone / volume defined by the boundary wall.

16 (Previously presented) A sterile air trolley as claimed in claim 14, wherein the shape of the tray is rectangular, with the boundary wall defining the four sides of the rectangle and wherein the filtered air is emitted inwardly over the work surface from all four sides.

17. (Previously presented) A sterile air trolley as claimed in claim 16, wherein the trolley casing is in a modular form having a base unit housing the impeller and an upper unit comprising the tray-shaped work surface and boundary wall, the upper unit being readily demountable from and re-mountable to the base unit.

18. (Currently amended) A sterile air trolley as claimed in claim 17, ~~wherein~~ further comprising sterilized surgical instruments ~~are set out on the work surface of the upper unit and sealed in by a film, foil or lid of barrier material that is mounted above the work surface.~~

19. (Previously presented) A sterile air trolley as claimed in claim 18, wherein the height of the boundary wall is slightly greater than the height of the any of the instruments or other items placed flat on the work surface of the tray in order to fully enshroud the same.

20. (New) A sterile air trolley as claimed in claim 1, wherein no air outlets are directed upwardly or outwardly.

21. (New) A sterile air trolley as claimed in claim 14, wherein no air outlets are directed upwardly or outwardly.